Package: shinythemes (via r-universe)

October 20, 2026

Title Themes for Shiny

Version 1.2.0

Description Themes for use with Shiny. Includes several Bootstrap themes from <https://bootswatch.com/>, which are packaged for use with Shiny applications.

Depends R (>= 3.0.0)

Imports shiny (>= 0.11)

URL https://rstudio.github.io/shinythemes/

License GPL-3 | file LICENSE

RoxygenNote 7.1.1

Config/pak/sysreqs cmake make libuv1-dev

Repository https://posit-dev-shinycoreci.r-universe.dev

Date/Publication 2022-02-25 15:37:48 UTC

RemoteUrl https://github.com/rstudio/shinythemes

RemoteRef HEAD

RemoteSha 492b6aa7ce096e986dd8b5958f8fb38315e5e4a4

Contents

shinytheme 2
shinythemes 2
themeSelector 5

Index **7**

shinytheme *Return the URL for a Shiny theme*

Description

The result of this function should be used as the theme argument for bootstrapPage, fluidPage, navbarPage, or fixedPage.

Usage

```
shinytheme(theme = NULL)
```

Arguments

theme	Name of a theme.

See Also

The main shinythemes page for information about available themes and more detailed examples.

Examples

```
## Not run:
shinyApp(
  ui = fluidPage(theme = shinytheme("united"),
    ...
  ),
  server = function(input, output) { }
)

## End(Not run)
```

shinythemes *Themes for Shiny*

Description

This package contains Bootstrap themes from https://bootswatch.com/, which are packaged for use with Shiny applications. The themes included are:

Details

- cerulean
- cosmo
- cyborg
- darkly
- flatly
- journal
- lumen
- paper
- readable
- sandstone
- simplex
- slate
- spacelab
- superhero
- united
- yeti

To use the themes, use the `theme` argument to `bootstrapPage`, `fluidPage`, `navbarPage`, or `fixedPage`. The value should be `shinytheme("cerulean")`, where the theme name takes the place of `"cerulean"`.

Examples

```
## Not run:
library(shiny)
library(shinythemes)

# A very basic navbar page with different themes
shinyApp(
  ui = navbarPage("Default theme",
    tabPanel("Plot", "Plot tab contents..."),
    navbarMenu("More",
      tabPanel("Summary", "Summary tab contents..."),
      tabPanel("Table", "Table tab contents...")
    )
  ),
  server = function(input, output) { }
)

shinyApp(
  ui = navbarPage("United",
    theme = shinytheme("united"),
    tabPanel("Plot", "Plot tab contents..."),
    navbarMenu("More",
      tabPanel("Summary", "Summary tab contents..."),
      tabPanel("Table", "Table tab contents...")
```

```
    )
  ),
  server = function(input, output) { }
)

shinyApp(
  ui = navbarPage("Cerulean",
    theme = shinytheme("cerulean"),
    tabPanel("Plot", "Plot tab contents..."),
    navbarMenu("More",
      tabPanel("Summary", "Summary tab contents..."),
      tabPanel("Table", "Table tab contents...")
    )
  ),
  server = function(input, output) { }
)


# A more complicated app with the flatly theme
shinyApp(
  ui = fluidPage(
    theme = shinytheme("flatly"),
    titlePanel("Tabsets"),
    sidebarLayout(
      sidebarPanel(
        radioButtons("dist", "Distribution type:",
                     c("Normal" = "norm",
                       "Uniform" = "unif",
                       "Log-normal" = "lnorm",
                       "Exponential" = "exp")),
        br(),
        sliderInput("n", "Number of observations:",
                     value = 500, min = 1, max = 1000)
      ),
      mainPanel(
        tabsetPanel(type = "tabs",
          tabPanel("Plot", plotOutput("plot")),
          tabPanel("Summary", verbatimTextOutput("summary")),
          tabPanel("Table", tableOutput("table"))
        )
      )
    )
  ),
  server = function(input, output) {
    data <- reactive({
      dist <- switch(input$dist,
                     norm = rnorm,
                     unif = runif,
                     lnorm = rlnorm,
                     exp = rexp,
                     rnorm)
      dist(input$n)
    })
```

```
    output$plot <- renderPlot({
      dist <- input$dist
      n <- input$n
      hist(data(), main=paste('r', dist, '(', n, ')', sep=''))
    })

    output$summary <- renderPrint({
      summary(data())
    })

    output$table <- renderTable({
      data.frame(x=data())
    })
  }
)

## End(Not run)
```

`themeSelector` *Add a theme selector widget in a floating panel*

Description

This adds a widget for selecting the theme, in a floating panel. It is meant for use during the development phase of a Shiny application.

Usage

```
themeSelector()
```

Details

This can be inserted anywhere inside of the application, although if it is put inside a tab, it will be visible only when that tab is showing. For it to show at all times, it must be used outside a tab.

Examples

```
if (interactive()) {
# themeSelector can be inserted anywhere in the app.
shinyApp(
  ui = fluidPage(
    shinythemes::themeSelector(),
    sidebarPanel(
      textInput("txt", "Text input:", "text here"),
      sliderInput("slider", "Slider input:", 1, 100, 30),
      actionButton("action", "Button"),
      actionButton("action2", "Button2", class = "btn-primary")
    ),
    mainPanel(
```

```
      tabsetPanel(
        tabPanel("Tab 1"),
        tabPanel("Tab 2")
      )
    )
  ),
  server = function(input, output) {}
)


# If this is used with a navbarPage() or other type of page where there is not a
# good place to put it where it is outside of all tabs, you can wrap the entire
# page in tagList() and make the themeSelector a sibling of the page.
shinyApp(
  ui = tagList(
    shinythemes::themeSelector(),
    navbarPage(
      "Theme test",
      tabPanel("Navbar 1",
        sidebarPanel(
          textInput("txt", "Text input:", "text here"),
          sliderInput("slider", "Slider input:", 1, 100, 30),
          actionButton("action", "Button"),
          actionButton("action2", "Button2", class = "btn-primary")
        ),
        mainPanel(
          tabsetPanel(
            tabPanel("Tab 1"),
            tabPanel("Tab 2")
          )
        )
      ),
      tabPanel("Navbar 2")
    )
  ),
  server = function(input, output) {}
)
}
```

Index

bootstrapPage, *2, 3*

fixedPage, *2, 3*
fluidPage, *2, 3*

navbarPage, *2, 3*

shinytheme, 2
shinythemes, 2, *2*

themeSelector, 5